Drive & Feed End Modules



Standard 8" Profile

Fill in _ _ with 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 36, 42, 48, 54 or 60 for conveyor width

Drive Modules	Options	Part Number	Functions / Features / Construction
External Mount Motor and Control	Single Speed 10, 14, 19, 29, 34, 47, 57 RPM Variable Speed 2-10, 3-14, 3-20, 5 -30, 5-35, 10-50, 10-58 FPM	HDSE	 Available for all widths 115V Brushless Stainless steel shaft Required for water applications Requires 3' of belt
Internal Mount Motor	Single Speed 10, 14, 19, 29. 34, 47, 57 FPM Variable Speed 2-10, 3-14, 3-20, 5 -30, 5-35, 10-50, 10-58 FPM	HDSI	 Available for 12" - 22" and 26" - 36" widths 115V Brushless Stainless steel shaft Requires 3' of belt
External Mount AC Variable Frequency Motor	Variable Speed 10-60 FPM	HDVEVFD	 Available for all widths 110/60/1ph, 230/60/1ph or 460/60/3ph 500 in lb/155 torque Brushless Stainless steel shaft Requires 3' of belt
External Mount Radius Turn Motor	Single Speed 10, 14, 19, 29, 34, 47, 57 FPM Variable Speed 2-10, 3-14, 3-20, 5-30, 5-35, 10-50, 10-58 FPM	RTSSE	 Available for radius turn conveyors Brushless Stainless steel shaft Requires 3' belt Indexing and reversing options not available
Feed End Modules Feed End Module	Options	Part Number TENX	 Functions / Features / Construction Begins the return end of a conveyor system Required in all systems Requires 4' of belt
Heavy Duty Feed End Module		TENXHD	 Typically used on conveyors that require more than 100 square feet of belting External adjustment mechanism Requires 4' of belt

1.800.640.6850